




短节距精密滚子链链轮

Short pitch precision roller chain wheels


<p>2"×1 1/4 32A-1-2-3 GB1244-1997 DIN8187 ISO/R606</p> 	链轮齿部参数MM		
	节距	P	50.8
	滚子直径	d-φ	28.58
	元弧半径	r3	54
	倒角宽度	C	7
	齿宽	B1	29.3
	齿宽	b1	28.8
	齿宽	B2	87.89
	B3	146.44	



A型单排平片链轮
A type simplex plate wheels



A型双排平片链轮
A type duplex plate wheels



A型叁排平片链轮
A type triplex plate wheels

齿数 Z	外径 de	节径 dp	单排链轮			双排链轮			叁排链轮		
			Simplex			Duplex			Triplex		
			dm	D1	A	dm	D2	A	dm	D3	A
8	153.2	132.69	85	30	80	82	25	130	82	25	180
9	169	148.54	100	30	80	88	25	130	88	25	180
10	185	164.44	115	30	80	104	25	130	104	25	180
11	200.8	180.34	125	30	80	120	30	130	120	30	180
12	216.8	196.29	133	30	80	140	30	140	133	30	180
13	232.8	212.29	145	30	80	140	30	140	145	30	180
14	248.8	228.29	145	30	80	140	30	140	145	30	180
15	264.8	244.3	145	30	80	140	30	140	160	30	180
16	280.9	260.4	160	30	90	140	30	140	160	30	180
17	296.9	276.4	160	30	90	140	30	140	180	30	180
18	313	292.55	160	30	90	140	30	140	180	30	180
19	329.1	308.66	160	30	90	140	30	140	200	30	180
20	345.2	324.71	180	30	90	140	30	140	200	30	180
21	361.3	340.82	180	40	90	140	30	140	200	40	180
22	377.5	356.98	180	40	90	140	30	140	200	40	180
23	393.6	373.08	180	40	90	140	30	140	200	40	180
24	409.7	389.18	180	40	90	140	30	140	200	40	180
25	425.8	405.33	180	40	90	140	30	140	200	40	180
26	441.9	421.44	180	40	90	140	30	140	200	40	180
27	458.1	437.59	180	40	90	140	30	140	200	40	180
28	474.2	474.2	180	40	90	140	30	140	200	40	180
29	490.4	490.4	180	40	90	140	30	140	200	40	180
30	506.5	506.5	180	40	90	140	30	140	200	40	180
31	525	502.13	200	40	90	150	40	140	200	40	180
32	541	518.26	200	40	90	150	40	140	200	40	180
33	557	534.42	200	40	90	150	40	140	200	40	180
34	573	550.56	200	40	90	150	40	140	200	40	180
35	589	566.71	200	40	90	150	40	140	200	40	180
36	605	582.86	200	40	90	150	40	140	200	40	180
37	622	599.01	200	40	90	150	40	140	200	40	180
38	638	615.16	200	40	90	150	40	140	200	40	180
39	654	631.31	200	40	90	150	40	140	200	40	180
40	670	647.47	200	40	90	150	40	140	200	40	180
45	751	728.24	200	45	90	150	40	140	200	40	180
50	832	809.04	220	45	90	150	40	140	200	40	180
55	919	889.84	220	45	90	150	40	140	200	40	180
60	1000	970.65	220	45	90	150	40	140	200	40	180

